



**S.F. No. 2166, as introduced - 87th Legislative Session (2011-2012) [12-4005]**

2.1 Sec. 2. Minnesota Statutes 2010, section 169.4501, subdivision 2, is amended to read:

2.2 Subd. 2. **Applicability.** (a) The standards adopted in this section and sections  
2.3 169.4502 and 169.4503, govern the construction, design, equipment, and color of school  
2.4 buses used for the transportation of school children, when owned or leased and operated  
2.5 by a school or privately owned or leased and operated under a contract with a school.  
2.6 Each school, its officers and employees, and each person employed under the contract is  
2.7 subject to these standards.

2.8 (b) The standards apply to school buses manufactured after December 31, ~~2007~~  
2.9 2012. Buses complying with the standards when manufactured need not comply with  
2.10 standards established later except as specifically provided for by law.

2.11 (c) A school bus manufactured on or before December 31, ~~2007~~ 2012, must conform  
2.12 to the Minnesota standards in effect on the date the vehicle was manufactured except as  
2.13 specifically provided for in law.

2.14 (d) A new bus body may be remounted on a used chassis provided that the remounted  
2.15 vehicle meets state and federal standards for new buses which are current at the time of the  
2.16 remounting. Permission must be obtained from the commissioner of public safety before  
2.17 the remounting is done. A used bus body may not be remounted on a new or used chassis.

2.18 Sec. 3. Minnesota Statutes 2010, section 169.4503, subdivision 5, is amended to read:

2.19 Subd. 5. **Colors.** Fenderettes may be black. The beltline may be painted yellow  
2.20 over black or black over yellow. The rub rails shall be black. The area around the lenses  
2.21 of alternately flashing signal lamps extending outward from the edge of the lamp three  
2.22 inches, plus or minus one-quarter inch, to the sides and top and at least one inch to the  
2.23 bottom, shall be black. Visors or hoods, black in color, with a minimum of four inches  
2.24 may be provided.

2.25 Sec. 4. Minnesota Statutes 2010, section 169.4503, subdivision 20, is amended to read:

2.26 Subd. 20. **Seat and crash barriers.** ~~(a)~~ All restraining barriers and passenger seats  
2.27 shall be covered with a material that has fire retardant or fire block characteristics.

2.28 ~~(b) All seats must have a minimum cushion depth of 15 inches and a seat back~~  
2.29 ~~height of at least 20 inches above the seating reference point, and beginning October 21,~~  
2.30 ~~2009, must also conform to the Federal Motor Vehicle Safety Standard in Code of Federal~~  
2.31 ~~Regulations, title 49, section 571.222.~~

2.32 Sec. 5. Minnesota Statutes 2010, section 169.4503, is amended by adding a subdivision  
2.33 to read:

**S.F. No. 2166, as introduced - 87th Legislative Session (2011-2012) [12-4005]**

3.1            Subd. 28. **Auxiliary fans.** Additional auxiliary fans are required for school buses  
3.2 manufactured on or after December 31, 2012, and shall meet the following requirements:

3.3            (1) fans for the left and right sides of the windshields shall be placed in a location  
3.4 where they can be adjusted for maximum effectiveness and where they do not obstruct  
3.5 vision to any mirror. Type A buses may be equipped with one fan;

3.6            (2) fans shall be a minimum of six inches in diameter;

3.7            (3) fan blades shall be covered with a protective cage; and

3.8            (4) each fan shall be controlled by a separate switch.

3.9            Sec. 6. Minnesota Statutes 2010, section 169.4503, is amended by adding a subdivision  
3.10 to read:

3.11            Subd. 29. **Video/mobile surveillance systems.** Camera heads for video/mobile  
3.12 surveillance may be mounted in the driver compartment area, mid-bus, or on a rear interior  
3.13 bulkhead in the student passenger area. For buses manufactured or retrofitted with a  
3.14 surveillance system after December 31, 2012, cameras mounted mid-bus must be parallel  
3.15 to a seat back, must not have any sharp edges, must not extend outward more than three  
3.16 inches, and must be located within 24 inches of the top of the side window of the bus.

3.17            Sec. 7. **REPEALER.**

3.18            Minnesota Statutes 2010, section 169.454, subdivision 10, is repealed.