

1341.1004 A117.1 SECTION 1004, TYPE B UNITS.

Subpart 1. **A117.1 Section 1004.4.2, Changes in level.** A117.1 section 1004.4.2 is amended to read as follows:

1004.4.2 Changes in Level. Changes in level shall comply with section 303.

Exception: Where exterior deck, patio, or balcony surface materials are impervious, the finished exterior impervious surface shall be 2 inches (50 mm) maximum below the floor level of the adjacent interior spaces of the unit.

Subp. 2. [Repealed, 39 SR 95]

Subp. 3. **A117.1 Section 1004.11, Toilet and Bathing Facilities.** A117.1 section 1004.11.3.1.3.1, Parallel approach bathtubs, is amended to read as follows:

1004.11.3.1.3.1 Parallel Approach Bathtubs. A clearance 60 inches (1525 mm) minimum in length and 30 inches (760 mm) minimum in width shall be provided in front of bathtubs with a parallel approach. Lavatories complying with section 606 shall be permitted at the control end of the clearance. A lavatory complying with section 1004.11.3.1.1 or a water closet shall be permitted at one end of the bathtub if a clearance 48 inches (1220 mm) minimum in length and 30 inches (760 mm) minimum in width for a parallel approach is provided in front of the bathtub.

Statutory Authority: *MS s 16B.37; 16B.59 to 16B.76; 326B.02; 326B.101; 326B.106*

History: *32 SR 9; 39 SR 95*

Published Electronically: *January 27, 2015*