

CHAPTER 299G

PROTECTION OF BUILDINGS AND OCCUPANTS

299G.13 Safety glazing; definitions.

299G.13 SAFETY GLAZING; DEFINITIONS.

[For text of subs 1 and 2, see M.S.1982]

Subd. 3. "Hazardous locations" means those structural elements, glazed or to be glazed, in residential buildings and other structures used as dwellings, commercial buildings, industrial buildings, and public buildings, known as interior and exterior commercial entrance and exit doors, and the immediately adjacent operable and inoperable glazed panels, sliding glass door units including the fixed glazed panels which are part of such units, storm or combination doors, shower and bathtub enclosures, primary residential entrance and exit doors and the operable and inoperable adjacent sidelites, whether or not the glazing in such doors, panels and enclosures is transparent.

[For text of subs 4 to 9, see M.S.1982]

Subd. 10. "Operable and inoperable glazed panels immediately adjacent to entrance or exit doors" means the flat glazed panels on either or both sides of interior or exterior doors, and within the same wallplane as the door, whose nearest vertical edge is within 12 inches of the door in a closed position and whose bottom edge is less than 60 inches above the floor or walking surface.

[For text of subs 11 to 16, see M.S.1982]

History: 1983 c 228 s 2,3